



FEATURES

- Porous stones available
- -40°C to +80°C Operating Temperature
- Accuracy up to $\pm 0.5\%$

APPLICATIONS

- Pore Water Measurement
- Centrifuge
- Laboratory

EPB-PW

Miniature Pressure Transducer

SPECIFICATIONS

- Miniature design (body $\varnothing 6.4$ mm)
- Titanium Construction
- EMI Protected per CE Compliance
- IP68 Ingress Protection
- Sealed Gauge reference

The **EPB-PW** pressure transducer is specifically designed for pore water applications in either centrifuges or laboratory equipment. Using either ceramic or bronze sintered filters, the sensor can be used on clay or sand-based materials.

Made of titanium, the **EPB-PW** provides a rugged construction and is not affected by external clamping forces when fitted. Having a miniature design of 6.4 x 11.4mm ensures it is backwards compatible with other older manufacturers' products.

This miniature pressure transducer features an **IP68** rating, flexible cable and is available with options such as a **PT1000** temperature sensor upon request.

The standard version is suitable for many applications, but the dedicated design team at our Transducer Engineering Centre stands ready to provide a custom design as required.

On request, Instruction documents can be provided to ease the selection and use of our sensors and provide helpful tips.

STANDARD RANGES



Ranges (FS)		Pressure Reference Sealed	Pressure Limit	Sensitivity "FSO" (nom.)	CNL&H (%FS)	Thermal Zero Shift "TZS" (/50°C)
bar	psi					
1	15	•	4.5 x FS	5 mV/V	±1%	±4% FSO
1.5	25	•	3 x FS	7.5 mV/V	±1%	±2% FSO
3.5	50	•	2 x FS	10 mV/V	±1%	±2% FSO
7	100	•	2 x FS	12.5 mV/V	±0.5%	±1.5% FSO
15	250	•	2 x FS	12.5 mV/V	±0.5%	±1.5% FSO
35	500	•	2 x FS	12.5 mV/V	±0.5%	±1.5% FSO
70	1K	•	2 x FS	12.5 mV/V	±0.5%	±1.5% FSO

PERFORMANCE SPECIFICATIONS (typical values at temperature 23±3°C)

PARAMETERS	VALUES
Supply Voltage	1 to 10Vdc regulated
Input Resistance	1000Ω nom.
Output Resistance	400Ω nom.
Non-Repeatability	±2.5% FSO
Thermal Sensitivity Shift "TSS" in CTR	±2% / 50°C [1/100 ° F]
Operating Temperature Range (OTR)	-40°C to 80°C [-40 to 170 ° F]
Compensated temperature Range (CTR)	0°C to 60°C [32 to 140 ° F]
Zero Offset	± 10 mV
Ingress Protection	IP68 – 10 meters (1bar)
CE conformance according to	EN 61010-1, EN 50081-1, EN 50082-1

Sensors are calibrated with 10Vdc power supply as standard.
 For custom configurations, consult factory.

DIMENSIONS & WIRING SCHEMATIC (IN METRIC)



OPTIONS

Z0 : Compensation Temperature Range -40 to 20°C [-40 to 70°F]
V5 : Excitation 5 Vdc and signal 50% of the FSO range
PCxx : Porous Ceramic installed. Replace “xx” by air entry value 0.5; 1; 3 or 5 bar
V00 : Non-standard power supply calibration, replace “00” with value in Volt (standard 10Vdc)
L00M : Special cable length, replace “00” with total length in meters

ORDERING INFORMATION

EPB-PW	-	20B	S	-	/L5M
Model	-	Pressure Range	Pressure reference	-	Options
EPB-PW		1B 1.5B 3.5B 7B 15B 35B 70B	15P 25P 50P 100P 250P 500P 1KP	S : sealed	Z0 V5 L00M

RECOMMENDED ACCESSORIES

Description	Air entry value	Maximum pore size	Part Number
PC : Porous Ceramic with air entry from 0.5 to 5 bar ordered separately	Porous Ceramic 0.5 bar	6.0 µm	ZPBS6220040.5
	Porous Ceramic 1 bar	2.5 µm	ZPBS6220041
	Porous Ceramic 3 bar	0.7 µm	ZPBS6220043
	Porous Ceramic 5 bar	0.5 µm	ZPBS6220045
BF : Bronze Filter	Consult factory	Consult factory	Consult factory

NORTH AMERICA

Measurement Specialties, Inc.,
a TE Connectivity company
45738 Northport Loop West
Fremont, CA 94538
Tel: +1 800 767 1888
Fax: +1 510 498 1578
customercare.frmt@te.com

EUROPE

MEAS France SAS,
a TE Connectivity company
26 Rue des Dames
78340 Les Clayes-sous-Bois, France
Tel: +33 (0) 130 79 33 00
Fax: +33 (0) 134 81 03 59
customercare.lcsb@te.com

ASIA

Measurement Specialties (China) Ltd.,
a TE Connectivity company
No. 26 Langshan Road
Shenzhen High-Tech Park (North) Nanshan
District, Shenzhen, 518057
China
Tel: +86 755 3330 5088
Fax: +86 755 3330 5099
customercare.shzn@te.com

TE.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties, TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2015 TE Connectivity Ltd. family of companies All Rights Reserved.